


1. REFERENCE SYMBOL : (SEE FLOOR PLANS).

 LETTER INDICATES PARTITION TYPE - SEE BELOW.

 DOUBLE SQUARE INDICATES ACOUSTICAL PARTITION.  
SAME AS "1", EXCEPT WITH BATT INSULATION, SEALANT  
AT PERIMETER, AND CUT-OUTS OF PARTITION.

2. ALONG A CONTINUOUS STRING OF PARTITIONS, THE CONTINUOUS FINISH SURFACE IS TO ALIGN.
3. USE 5/8" TYPE "X" GYPSUM WALL BOARD THROUGHOUT, UNLESS OTHERWISE SURFACE IS TO ALIGN.
4. GYPSUM WALL BOARD ATTACHED BELOW COMPENSATION CHANNEL AT HEAD CONDITION.
5. FOR VARIOUS CONDITIONS WHERE A RATED PARTITION MEETS THE UNDERSIDE OF METAL DECKING, SEE TYPICAL DETAILS & ,THIS SHEET.
6. STUD SPACING @ 16" O.C., U.O.N.
7. PROVIDE 20 GA. METAL STUDS - TYPICAL, U.O.N.

## PARTITION NOTES

3" = 1'-0"

A710-0

### ARCHITECTURAL STANDARD DETAILS PARTITION NOTES

UNIVERSITY OF CALIFORNIA - LAWRENCE BERKELEY NATIONAL LABORATORY  
FACILITIES DEPARTMENT

DRAWN BY  
STK/WC

DATE  
8/8/98

APPROVED BY

DATE

DRAWING FILE NAME  
A710-0

DETAIL TYPE  
PARTS

SCALE

SHEET

A710-0